

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in this application:

Claim 1 (currently amended): A bandwidth-adaptive method for synchronizing display data between a source node and a plurality of consumer nodes, the method comprising:

- (a) identifying, by a source node, a change in local display data;
  - (b) creating, by the source node, at least one data packet representing the change in local display data;
  - (c) receiving, by a communications service from the source node, a metadata information packet identifying data packets that represent a current state of local display data following the change in local display data, the metadata packet being a separate packet from the identified data packets;
  - (d) receiving, by the communications service from the source node, at least one of the identified data packets;
  - (e) selecting, by the communications service, first and second sets of the identified data packets responsive to the received metadata information packet, the first and second sets being different from one another;
  - (f) transmitting, by the communications service to a first consumer node, the metadata information and packet along with the first set of identified data packets; and
  - (g) transmitting, by the communications service to a second consumer node having a different bandwidth connection with the communications service than the first consumer node has with the communications service, the metadata information and packet along with the second set of identified data packets,
- whereby the first and second consumer nodes are transmitted a common metadata packet, but different data packets along therewith.

Claim 2 (currently amended): The method of claim 1 further comprising receiving, by the communications service prior to selecting a set of the identified data packets responsive to the received metadata information packet, a request from a consumer node for the current state of the source node local display data.

Claim 3 (previously presented): The method of claim 2 further comprising repeating (a) through (d) until the request is received from the consumer node for the current state of the source node local display data.

Claim 4 (currently amended): The method of claim 3 wherein selecting a set of the identified data packets responsive to the received metadata ~~information~~packet comprises:

(e-a) selecting one of the metadata ~~information~~packets received by the communications service; and

(e-b) selecting at least one of the data packets received by the communications service and identified by the selected metadata ~~information~~packet.

Claim 5 (currently amended): The method of claim 1 wherein selecting a set of the identified data packets responsive to the received metadata ~~information~~packet comprises selecting a plurality of the identified data packets responsive to the received metadata ~~information~~packet.

Claim 6 (previously presented): The method of claim 5 wherein transmitting to the first consumer node the first set of identified data packets comprises transmitting to the first consumer node a first plurality of data packets selected therefor, and wherein transmitting to the second consumer node the second set of identified data packets comprises transmitting to the second consumer node a second plurality of data packets selected therefor.

Claim 7 (previously presented): The method of claim 1 wherein receiving, by the communications service from the source node, the at least one of the identified data packets comprises receiving, by the communications service from the source node, at least one of the identified data packets in encrypted form.

Claim 8 (currently amended): The method of claim 1 further comprising storing the metadata ~~information~~packet received by the communications service in a memory device.

Claim 9 (previously presented): The method of claim 1 further comprising storing at least one of the data packets received by the communications service in a memory device.

Claim 10 (currently amended): The method of claim 9 further comprising selecting at least one of the stored data packets responsive to the metadata ~~information~~packet received by the communications service.

Claim 11 (previously presented): The method of claim 10 further comprising transmitting to one of the first and second consumer nodes the selected at least one of the stored data packets.

Claim 12 (previously presented): The method of claim 1 further comprising storing, in a memory element, information identifying a data packet transmitted to one of the first and second consumer nodes.

Claim 13 (currently amended): The method of claim 12 further comprising selecting at least one of the data packets received by the communications service that is responsive to the metadata ~~information packet~~ received by the communications service and to the stored information identifying the data packet transmitted to the one of the first and second consumer nodes.

Claim 14 (currently amended): A bandwidth-adaptive system for synchronizing display data between consumer nodes and a source node, the system comprising:

a source node configured to i) identify a change in local display data, ii) create at least one data packet representing the change in local display data, iii) create a metadata packet identifying data packets that represent a current state of the local display data, the metadata packet being a separate packet from the identified data packets, and iv) transmit the metadata packet and at least one of the identified data packets; and

a communications service in communication with the source node, the communications service configured to

(a) select i) a first set of the identified data packets for transmission, along with the metadata packet, to a first consumer node, and ii) a second set of the identified data packets, different from the first set, for transmission, along with the metadata packet, to a second consumer node having a different bandwidth connection with the communications service than the first consumer node has with the communications service; and

(b) transmit the metadata packet and the first and second sets of identified data packets such that the first and second consumer nodes are transmitted a common metadata packet, but different data packets along therewith.

Claim 15 (previously presented): The system of claim 14 further comprising the first consumer node, the first consumer node configured to request the current state of the source node local display data from the communications service.

Claim 16 (previously presented): The system of claim 15 wherein the communications service is further configured to select the first set of identified data packets in response to the request made by the first consumer node.

Claim 17 (previously presented): The system of claim 15 further comprising the second consumer node, the second consumer node configured to request the current state of the source node local display data from the communications service.

Claim 18 (previously presented): The system of claim 17 wherein the source node is further configured to transmit a plurality of metadata packets, each of the plurality of metadata packets representing one state of the source node local display data.

Claim 19 (previously presented): The system of claim 18 wherein the communications service is further configured to select a first metadata packet for transmission to the first consumer node and a second metadata packet for transmission to the second consumer node.

Claim 20 (previously presented): The system of claim 14 wherein the communications service further comprises a memory element.

Claim 21 (original): The system of claim 20 wherein the memory element is a persistent storage device.

Claim 22 (previously presented): The system of claim 20 wherein the communications service is further configured to store the metadata packet in the memory element.

Claim 23 (previously presented): The system of claim 20 wherein the communications service is further configured to store at least one identified data packet in the memory element.

Claim 24 (previously presented): The system of claim 20 wherein the communications service is further configured to store in the memory element information regarding transmission of data packets to at least one of the first and second consumer nodes.

Claim 25 (previously presented): The system of claim 14 wherein the source node is further configured to encrypt a data packet before transmission.

Claim 26 (currently amended) A bandwidth-adaptive method for synchronizing display data between a source node and a plurality of consumer nodes, the method comprising:

- (a) identifying, by a source node, a first change in local display data;
- (b) receiving, by a communications service from the source node, first metadata information identifying a first at least one data packet representing a first state of local display data following the first change in local display data;
- (c) identifying, by the source node, a second change in local display data;
- (d) receiving, by the communications service from the source node, second metadata information identifying a second at least one data packet representing a second state of local display data following the second change in local display data;
- (e) generating, by the communications service, ~~third metadata information representing~~ by determining the difference between the first at least one identified data packet metadata information and the second at least one identified data packet, the metadata information, third metadata information identifying a third at least one data packet;
- (f) transmitting, by the communications service to a consumer node, the third metadata information; and
- (g) transmitting, by the communications service to the consumer node, the third at least one data packet.